

# ***SPEEDIO***

**S300Xd2**

**S500Xd2**

**S700Xd2**

Compact Machining Center



# S

## SPEEDIO's bestselling model further expands the range of application

An extensive range of magazine specifications, including the newly developed 100-tool magazine, spindle specifications, simultaneous 5-axis specifications and enlarged machining area.

A wide range of specifications available to meet a wide variety of machining applications.

## Cutting Out the Waste *SPEEDIO*



S300Xd2

S500Xd2

S700Xd2

Various magazine specifications




Simultaneous 5-axis machining



Various spindle specifications



Enlarged machining area




Basic specifications		Required floor space (mm)	
Max. spindle speed <sup>3</sup> (min <sup>-1</sup> )	12,000 Optional: 10,000 high-torque Optional: 20,000, 27,000* <sup>1</sup>	S300Xd2	1,080 x 2,161
Travel of each axis (mm)	S300Xd2 X300 Y450 Z300 S500Xd2 X500 Y450 Z300/380* <sup>2</sup> S700Xd2 X700 Y450 Z300/380* <sup>2</sup> S700Xd2-100T X700 Y450 Z380	S500Xd2	1,560 x 2,081
Rapid traverse rate (m/min)	X/Y/Z 50/50/56	S700Xd2	2,050 x 2,081
		S700Xd2-100T	2,050 x 2,081
		Tool storage capacity (pcs.)	
		S300Xd2	14/21
		S500Xd2/S700Xd2	14/21/28
		S700Xd2-100T	100
		Simultaneous 5-axis spec. (5AX)	
		Available	

\*1. Cannot be selected for the Z-axis 380 mm spec. and the S700Xd2-100T. \*2. 380 is for Z-axis 380 mm spec. (optional). \*3. The 16,000min<sup>-1</sup> specification is discontinued as of March 2026.

## Most extensive range in its class provides best-fit solution for any type of application

A range of specifications are available with different X-axis travel, spindle type, or tool storage capacity.  
Selecting the best specifications for your application ensures that the SPEEDIO provides incomparable productivity for customers in any industry.

### Automobile



Inverter case  
Aluminum alloy  
Size: 440 x 280 x 150



Impeller  
Aluminum alloy  
Size:  $\phi 44 \times 21$




Large valve for thermal management  
Aluminum alloy  
Size: 230 x 170 x 40



EV gearbox housing  
Aluminum alloy  
Size: 305 x 260 x 90

### Semiconductor



Feeder frame  
Aluminum alloy  
Size: 600 x 250 x 12



Support bracket  
Stainless steel  
Size: 133 x 60 x 30

### Medical



Bone plate  
Ti-6Al-4V  
Size: 80 x 30 x 10

### Aircraft



Seat parts  
Aluminum alloy  
Size: 600 x 300 x 40

### Construction machinery



Valve plate  
Chrome molybdenum steel  
Size:  $\phi 160 \times 25$

## Increased travels of Y/Z axes and bigger table further expand the range of application

Increased travels of Y/Z axes, bigger table, and using a 28-tool magazine expand the range of application for process integration, such as for multi-face machining, and variable-product variable-volume production. Together with the extensive range of specifications, the machine responds to a wide variety of machining.

### Increased Y-axis travel

Increased Y-axis travel expands the range of target workpieces.

Y-axis travel **400mm<sup>\*1</sup>** ▶ **450mm**

### Bigger table

Bigger table expands the range of jig selection.

S300/S500Xd2 **600 x 400<sup>\*1</sup>** ▶ **600 x 450mm**  
 S700Xd2 **800 x 400<sup>\*1</sup>** ▶ **800 x 450mm**




\*1. Values of previous model

### Z-axis 380 mm spec. (optional)<sup>\*4</sup>

In addition to the standard 300 mm Z-axis travel, the 380 mm Z-axis travel can be selected. The Z-axis travel and the distance between the table top and spindle nose end have been increased to secure ample machining area in the Z-axis direction and improve tool accessibility.  
<sup>\*4.</sup> The Z-axis 380 mm spec. cannot be selected for the S300Xd2. Only Z-axis 380 mm spec. available on the S700Xd2-100T

Z-axis travel	
300mm (standard)	<b>380mm (optional)</b>
Distance between table top and spindle nose end	
180~480mm (standard)	<b>150~530mm (optional)</b>



\* When Z-axis 380 mm spec. is selected

### 28-tool magazine<sup>\*2</sup>

The 28-tool magazine is a compact turret magazine that achieves high-speed tool change. The maximum tool weight is 4 kg. An extensive range of magazine specifications are available, including 14-tool, 21-tool, 28-tool<sup>\*2</sup>, and 100-tool<sup>\*3</sup>.



#### 28-tool magazine

Max. tool diameter **110mm**  
 Max. tool weight **4kg**  
 Max. total tool weight **35kg**  
 Tool-Tool **0.7s**




\*2. The 28-tool magazine cannot be selected for the S300Xd2.

\*3. The 100-tool magazine can only be selected for the S700Xd2-100T. See pages 15 to 18 for details.

### Rotary table T-200Ad (optional)

A roller gear cam mechanism is used. Compared to a worm gear type, faster index machining is possible with higher accuracy. Optimal for process integration on the SPEEDIO.

Equipped with a function that enables indexing at the optimal acceleration based on the estimated inertia.



\* Photo shows the S700Xd2 Z-axis 380 mm spec.

## Untiring pursuit of high productivity

### Reduction in waste by optimized control through machine/controller integrated development

Optimized control by the CNC-D00 controller eliminates waste to the utmost limit in every operation during machining. This maximizes the performance of the highly reliable machine and ensures high productivity.

#### Non-stop ATC

High-speed tool change has been achieved by faster and optimized spindle start/stop, Z-axis up/down, and magazine operation. Tools up to 3 kg can be changed in the shortest time. Tools up to 4 kg can also be changed with minimal increase in time.


	14/21 tools (Standard tools)	28 tools (Standard tools)	28 tools (Heavy tools)
Tool-Tool	<b>0.6s</b>	<b>0.7s</b>	<b>0.8s</b>
Chip-Chip*1	<b>1.2s</b>	<b>1.3s</b>	<b>1.4s</b>

\*1. Values for Z-axis 300 mm spec.

#### Magazine load conditions estimate\*2

Estimates the inertia and unbalanced load of the tool loaded in the magazine, and sets the optimum value for the acceleration of the magazine axis. In addition, automatically updates the value to the estimated optimum acceleration, even during programmed operation.

\*2. Cannot be used for tool stockers of the S700Xd2-100T.



#### High acceleration/deceleration spindle

Using a low inertia spindle and high acceleration/deceleration spindle motor has achieved faster spindle start/stop.

Spindle start/stop time **0.15s or less** \*High-torque spec.

#### High acceleration Z-axis

As the Z-axis moves frequently, the highest acceleration in its class has been achieved, contributing to reduction in cycle time.

Z-axis acceleration Max. **2.2G**


#### Improved automatic door opening/closing speed

The automatic door opening/closing speed has been improved, enabling significant reduction in setup time.

Automatic door opening/closing time **20% less**

#### Simultaneous operation

Wasted time has been reduced by simultaneously performing tool change and positioning X/Y and additional axes.



#### Optimal X/Y axes acceleration setting

Load weight is estimated by moving the table to set the optimal acceleration for the X/Y axes.







Table load weight estimate screen



#### Machining support without warmup

Equipped with an original measurement processing function that reduces the number of actual measurements by a touch probe according to the size of displacement. This eliminates the need for warmup operation, minimizing effects on productivity to achieve highly accurate machining.




# Extensive range of spindle specifications and NC functions support a wide variety of machining applications

A variety of spindles are available to meet a wide range of industries, from automobile to semiconductor, precision parts, and IT equipment industries. The NC unit achieves high-speed and highly accurate three-dimensional machining or simultaneous 5-axis machining\*1.

\*1. Simultaneous 5-axis machining is available only on the S300/500/700Xd2-5AX.

## Newly developed and highly efficient 20,000 min<sup>-1</sup> spindle motor

A new 20,000 min<sup>-1</sup> spindle motor has been developed. Compatible with the Coolant Through Spindle (CTS), this motor further improves productivity of small-diameter drilling. A variety of spindle specifications are available, including the standard 12,000 min<sup>-1</sup> spec. and high-torque spec.



<b>High-torque spec. (optional)</b>	
Max. torque	<b>92N·m</b>
Max. output	<b>26.2kW</b>
<b>20,000min<sup>-1</sup> spec. (optional)</b>	
Max. torque	<b>27N·m</b>
Max. output	<b>15.4kW</b>
<b>12,000 min<sup>-1</sup> spec. (standard)</b>	
Max. torque	<b>40N·m</b>
Max. output	<b>18.9kW</b>

## Improved spindle rigidity

For 10,000 min<sup>-1</sup> high-torque specifications (optional), the spindle bearing diameter has been enlarged to enhance rigidity. The machine demonstrates its capabilities in a wide variety of machining applications, including heavy-duty machining of steel.




<b>Spindle clamp force</b>
<b>Improved by 15%</b>
<b>Spindle bearing diameter (high-torque spec.)</b>
<b>Larger by 10%</b>

## Vibration adjustment (optional)

Vibration adjustment analyzes waveform data using a PC app to suggest the recommended spindle speed. Optimal machining conditions drive machining performance to the fullest.

[Conditions] Material: Aluminum Tool: ø10 end mill



## High-speed and highly accurate 3D machining using high-speed spindle and high accuracy mode

In addition to the highly-responsive servo control, the servo processing speed and resolution have been greatly improved. Enhanced original three-dimensional machining control, including increased look-ahead blocks and improved surface quality by the smooth path offset function, achieves high-speed and highly accurate three-dimensional machining.


<b>High-speed spindle spec. (optional)</b>	<b>27,000min<sup>-1</sup></b>
<b>High accuracy mode BII (optional)</b>	<b>Look-ahead 1,000 blocks</b>

## Simultaneous 5-axis machining

Equipped with a variety of functions, including tool center point control and submicron command, to achieve high-speed and highly accurate simultaneous 5-axis machining. \* Changing to the conversation language is not possible for the simultaneous 5-axis specifications (5AX).


### Tool center point control

Equipped with tool center point control where machining is performed by changing the tool direction relative to the workpiece. Optimal acceleration/deceleration by look-ahead up to 1,000 blocks achieves simultaneous 5-axis machining.



### Processing speed of minute line segments



The CPU capacity has been greatly increased to enhance the processing speed of minute line segments by four times the previous controller. This enables high-speed processing of CAM data with small tolerance.



### Productivity improvement

In addition to the compactness of the BT30, the original look-ahead acceleration/deceleration processing maximizes the machine's performance (max. speed and acceleration) to achieve high-speed simultaneous 5-axis machining.

Comparison with cycle time by a competitor's BT40 MC Workpiece: Impeller



### Z-axis motor

Acceleration of up to 2.2G contributes to reduction in cycle time.

### Magazine load conditions estimate

Sets the optimum value for the acceleration of the magazine axis.

### Spindle

Clamp force has been improved to enhance tool retention force.

### Column

Topology is used for the column shape. Reduces the influence of external vibration on the quality of the machined surface.

### Machine table

The table size has been expanded up to 450 mm in length. Jigs up to 400 kg can be loaded.

### Telescopic cover

A roof-shape that enhances chip evacuation performance is used to improve reliability.

### X/Y-axes motor

Using high resolution encoder and optimal acceleration setting achieves high speed and high accuracy.

### Base

The rib structure has been optimized through topology analysis. The rigidity when affected by external vibration has been improved.

### Example of machining difficult-to-cut material

	No. of revolutions [n]	Feed [vf]	Depth of cut [ap]
<b>Stainless steel</b> SUS316L	597min <sup>-1</sup>	477mm/min (18.8inch/min)	<b>2.5mm (0.10inch)</b>
<b>Pre-hardened steel</b> NAK80	597min <sup>-1</sup>	477mm/min (18.8inch/min)	<b>2.5mm (0.10inch)</b>

\* Values for the high-torque spec. The above machining capability may not be achieved depending on conditions, including usage environment, tools in use, and coolant. \* The machining capability table is provided on page 24.



## Reliability maintains high productivity

Maintenance functions have been enhanced to prevent machine failure, with measures for chips taken to reduce machining defects. Thorough avoidance of machine stoppage maintains high productivity at production sites.

### Enhanced maintenance functions


The machine is equipped with many functions that can prevent possible defects in daily production sites, such as chip problems, tool abrasion, omission of tool attachment, and re-machining of the same workpiece. These functions contribute to the reduction in wasted resources at production sites.

### Tool cleaning system (optional)

The number of discharge holes and the angle of these holes have been optimized to significantly increase the discharge flowrate. This has resulted in a threefold increase in cleaning capability, compared to the previous model.

CTS specifications allow the direct pump type where coolant is discharged from the CTS pump to be selected, consuming less air than the air-assisted type.

\* When CTS is not selected, air-assisted tool cleaning is used.



More discharge holes



\* Compared by removal rate of grease applied to taper

### Stuck chips detection function

Chips caught between the spindle and the holder during ATC are detected without using a sensor. Detecting any stuck chips during ATC prevents the outflow of defects. A retry function is also provided.

Tool No.	Tool name	Tool radius	Adjustment	Status
001	TOOL1	0.081	Normal	Value acquired
002	TOOL2	0.082	Normal	Value acquired
003	TOOL3	0.083	Normal	Value acquired
004	TOOL4	0.084	Normal	Value acquired
005	TOOL5	0.085	Normal	Value acquired
006	TOOL6	0.086	Normal	Value acquired
007	TOOL7	0.071	Chips stuck	Not acquired
008	TOOL8	0.082	Normal	Value acquired
009	TOOL9	0.083	Normal	Value acquired
010	TOOL10	0.083	Normal	Value acquired



### ATC tool monitoring

Checks the presence of a spindle tool before and after tool change, tool over spindle, positional shift of tool key etc. without using a sensor.



Spindle tool check




Key position deviation

### Machining load monitoring

Machining load applied to the spindle is monitored to issue an alarm when the load is not within the preset value.

Parameter number	001	002	003	004	005
Load monitor method	Standard	Preload	Set value	Set value	Set value
Time constant	0.01	0.02	0.03	0.04	0.05
Stop level for max.	Level 1	Level 2	Level 3	Level 4	Level 5
Stop level for min.	Level 1	Level 2	Level 3	Level 4	Level 5
Max. machining load	25.000	3.500	35.000	8.500	5.000
Min. machining load	3.000	1.000	2.000	2.000	2.000


Setting screen



Setting image


### Prevention of chip problems

Thorough chip evacuation/removal prevents chip problems, improving reliability. Increasing the number of chip shower nozzles and reviewing the diameter of the piping have improved chip evacuation performance.



More nozzles

### Image of chip evacuation flow






# Equipped with “CNC-D00” controller Enhanced usability with 15-inch LCD touch panel

Intuitive operation is possible with apps and vertical touch panel screen. Relevant functions are grouped according to purpose, such as setup and machining, leading to efficient operation. Production and operation states are visualized, allowing faster understanding. Waste-free operation is possible in setup, machining adjustment, production, and recovery process, leading to improved work efficiency and operating rate.


## Home screen

Information required for production, such as workpiece counter and tool life, is collected on the home screen. Shortcut keys are provided for screens frequently used so you can open them by one touch.




## User interface

Equipped with support apps with improved operability and visibility by grouping relevant functions and an easy-to-view display, in addition to several useful accessories (calculator, notebook, file viewer etc.). Operation on conventional screens is possible on the touch panel. With these, usability has been greatly improved.



## Setup support

Equipped with functions to easily perform setup, such as an ATC tool app that enables all magazine tool settings to be performed on one screen, menu programming that enables you to create NC programs by following instructions on the screen, and an on-screen help function.



## Machining adjustment support

Equipped with functions to easily perform optimal machining adjustment to improve productivity, such as a machining parameter adjustment app that enables you to easily adjust parameters according to machining details and a machining load waveform display/saving function.




## Production support

Equipped with functions to improve the operating rate, such as real time tool monitoring to eliminate defects, displaying production performance, power consumption etc. as a graph, and PLC/network functions to meet peripheral equipment and automation requirements.



## Recovery support

Equipped with functions to prevent failure or ensure quick recovery, such as maintenance time notice, displaying details when an alarm occurs, and guidance for recovery/check work.



## Equipped with functions that support connection with various peripheral equipment or automation


### Network

Sending/receiving files or monitoring via FTP or HTTP.  
Compatible with OPC UA, a data exchange standard for industrial communication.  
In addition to the conventional field bus, data communication is possible via Industrial Ethernet, such as Ethernet/IP and PROFINET.  
Production/operation results screens on the machine can be viewed from a PC's browser.

### Built-in PLC

Standard equipped with a PLC function. Program memory and object memory have been increased to enhance the capacity for peripheral equipment.  
In addition to ladder language, ST language and FBD language can also be used for built-in PLC programming.

## Built-in PLC screen



NC function video



Scan or Click


# Newly developed 100-tool magazine\*1 achieves space saving and high productivity

The new 100-tool magazine, featuring the largest storage capacity in the SPEEDIO series, has been developed.\*1

Brother's original mechanism achieves space saving and high productivity.

\*1. Mounted only on the S700Xd2-100T. Conversation language not available on the S700Xd2-100T.

## Newly developed 100-tool magazine (optional)



Left-side tool stocker      Turret magazine      Right-side tool stocker

A tool stocker that can store 36 tools is installed on the right and left sides of the 28-tool turret magazine, enabling storage of 100 tools, the largest capacity in the SPEEDIO series.

Brother's original tool handling mechanism achieves stable tool change.

100-tool magazine spec.	
Turret magazine	: 28 tools
Tool stocker (left/right)	: 36 tools each
Total storage capacity	: 100 tools

The stocker shutter separates the tool stocker from the machining chamber, minimizing the effect of chips on tools.



## Space-saving design

Tool stockers are installed inside the machine to save space while storing 100 tools.



\*2. Does not include coolant tank and chip conveyor

\*3. Compared to BT40 vertical MC with equivalent tool storage capacity

## High productivity

If the number of tools used in machining is 28 or less, high speed tool change is possible using only the turret magazine, leading to high productivity. Even when using tools in the tool stocker, handling is possible within approximately 5 seconds (1 tool).

In addition, all tools in the turret magazine can be easily changed, reducing setup time.

Turret magazine tool change time	
Tool to Tool:	0.7s
Chip to Chip:	1.4s

Tool stocker handling time*4	
Shortest (1 tool)	Approx. 5s*5
All tool change (28 tools)	Approx. 140s

\*4. Handling time varies depending on the tool attachment position.

\*5. Time for the tool at spindle position to be moved and changed with a tool in the tool stocker and for this tool to return to spindle position.



## Tool stocker management function

A function for managing the 100-tool magazine has been added to the ATC tool app.

Tool change operation is intuitive, and tools to be used in the machining program can be moved from the tool stocker to the turret magazine in a batch.

In addition, data of tools in the tool stocker can be easily changed.



Batch tool change

Tool setting screen

## 100-tool magazine\*1 and ample jig area increase efficiency of high-mix small-lot production and reduce manpower


In high-mix small-lot production, the magazine that can store up to 100 tools and ample jig area improve production efficiency and reduce manpower.

\*1. Mounted only on the S700Xd2-100T. Conversation language not available on the S700Xd2-100T.

### 100-tool magazine + Ample jig area


For high-mix small-lot workpieces, the 100-tool magazine eliminates the need for frequent tool changes, and the ample jig area enables multiple jigs to be mounted. These features significantly improve the efficiency of high-mix small-lot production.

#### Example of high-mix workpieces



Relay box

#### Example of jig mounting for three types of workpieces



### Making automation and manpower saving easier

#### Side shutter (optional)


Assuming loading/unloading of workpieces from the side by robots, a side shutter has been prepared to make automation easier.

\* A safety fence is required. Cannot be selected for the S300Xd2.



#### Chip conveyor (optional)

Two types of chip conveyors are available: scraper type and hinge + scraper type.



# SPEEDIO Blue Technology

Eliminating waste elements at production sites leads to reduction in greenhouse gas emissions, such as carbon dioxide and methane. Brother's optimal and compact design reduces wasted time, resources, and energy during parts machining.

We are striving to reduce environmental impact by conducting product life cycle assessment, which quantitatively evaluates environmental impact at each stage of production, transportation, use, disposal, and recycling.



## SPEEDIO Blue Technology Solves Four Waste Elements at Production Sites

### Wasted time reduction

Wasted time is reduced by minimizing non-cutting time in the machining cycle time and reducing setup time and downtime.

### Wasted resource reduction

Wasted resources are reduced by using machining adjustment support that prevents cutting defects and production support such as real-time monitoring.

### Wasted energy reduction

Optimal design eliminates all waste, including excessive power consumption and air flowrate, achieving industry-leading energy-saving performance.


### Wasted installation space reduction

Compact design reduces wasted space with less restrictions on installation locations.

## Wasted energy reduction

### Saving power

New functions, including chip shower energy savings operation, energy savings mode, and machining support without warmup, have been incorporated to significantly reduce power consumption, compared to the previous model. Together with various energy-saving technologies, such as power regeneration and highly efficient spindle motors, power consumption is overwhelmingly low.




Power consumption 30% less than previous model

\* Values taken by running sample program created by Brother with "chip shower energy savings operation" enabled

### Energy savings mode

Added a function to turn on/off energy-saving functions simultaneously. Items to be turned on/off can be customized.




- Standby mode
- Coolant pump
- Chip shower
- Work light
- Display off

Can be customized


### Chip shower energy savings operation

This function controls the on/off timing of the chip shower pump. Operation is switched via parameters according to the amount of chips discharged, contributing to energy saving for chip shower pumps that consume significant amounts of power.



### Power regeneration system

Equipped with a power regeneration system that recycles energy generated when a servo motor decelerates.



### Power consumption app


Servomotors, pumps, and other equipment are grouped and displayed according to purpose. Calculation is possible for each cycle.



- Highly efficient spindle motor
- Energy-saving pump
- LED work light

### Saving air

Air purge, spindle air blow, and other air-related functions have been reviewed and optimized to eliminate any waste. Compared to the previous model, air consumption is significantly reduced while maintaining reliability.




Air consumption 20% less than previous model

\* Values taken by running sample program created by Brother

### Air purge


Reinforced the labyrinth structure on the spindle end face to reduce air consumption.



Air flowrate analysis of spindle end face

### Spindle air blow


Optimized the air blow start/stop timing during tool change to reduce air consumption.



## Wasted resource reduction

### Tank with cyclone filter and no consumables (special option for CTS)

Clean coolant is returned to the clean tank through another tank with a cyclone filter that removes fine chips. Coolant is kept clean this way to reduce the filter change frequency and extend the service life of the pump.



### Automatic oil/grease lubricator that optimizes consumption (optional)


Consumption amount and timing are optimized by the automatic oil/grease lubricator. Oil mixing with coolant can be minimized.

#### Automatic oil lubricator




#### Automatic grease lubricator







**Coolant tank**  
Can be selected from 50L, 100L, 150L, or 200L according to the purpose. If you need a CTS spec. higher than 1.5 MPa, this will be custom-built.



**Chip conveyor**  
Two types of chip conveyors are available: scraper type and hinge + scraper type.



**Coolant Through Spindle (CTS)**  
Can be selected from 3.0 MPa or 7.0 MPa. Pump and tank are not included.




**Column coolant nozzle**  
Powerfully removes chips on and around the workpiece to prevent chips building up.



**Automatic door with switch panel 10 holes**  
A motor-driven door is used, achieving smooth operation.




**Area sensor**  
Optical area sensors are used. Use area sensors to prevent operators being caught in the automatic door.



**Side shutter**  
Assuming loading/unloading of workpieces from the side by robots, a side shutter has been prepared to make automation easier. \* A safety fence is required.



**Switch panel (8 holes or 10 holes)**  
Various switches, such as automatic door open/close switches, are set in specific locations. The switch panel (8 holes) is also available so that the position of the manual pulse connector can be changed.



**Head coolant nozzle**  
Coolant can reliably be applied to the machining section as the tool and nozzles are set in place.




**Chip shower**  
Chip shower piping is located at the upper section inside the machine for more efficient flow, and flexible shower nozzles can be directed to the side of the machine cover or sections where chips tend to accumulate.



**Tool cleaning system**  
High discharge pressure and flowrate powerfully removes chips stuck to the holder. Two types are available: air-assisted type and direct pump type where coolant is discharged directly from the CTS pump. \* The direct pump type can only be selected for CTS specifications.



**Fixture shower valve unit**  
Consists of jig washing valves and piping to the ceiling of the machine. Piping from the machine to the required location must be prepared by customers.



**Manual pulse generator**  
A cable is provided for the manual pulse generator, making setup easier. Equipped with emergency stop and enable switches.



**Tool breakage detector, touch type**  
A touch switch type tool breakage detector is available. \* Cannot be used for tool length measurement.




**Rotary table T-200Ad**  
Reduction in the body width secures a wider jig area. Use of the roller gear cam mechanism achieves high productivity, high accuracy, and extended service life.




**Spindle override**  
Spindle speed can be changed without changing the program.



**Cleaning gun**  
Helps clean the workpiece or chips inside the machine after machining.



**High column (150 mm, 250 mm)**  
150 mm and 250 mm high columns are available to meet customer's needs.



**Top cover**  
Shutting the opening on the top prevents coolant or chips splashing outside of the machine. A hole for the mist collector is provided.



**Side cover with transparent window**  
External light is drawn in to make the inside of the machine brighter and improve visibility. \* Order two covers when needed for both sides.




**Master on circuit**  
Master on circuit and switch can be attached. \* A switch panel (8 holes or 10 holes) is required separately.



**Data protection switch, key type**  
Changing the operation level is enabled or disabled by the key.



**Mist collector**  
Achieves a safe and hygienic work environment by capturing mist. Installed on the top of the control box.



**Touch probe**  
Zero-point measurements and similar operations can be performed using the probe. Measurement software and an optional datum sphere for measurement are available.



**Work light (1 or 2 lamps)**  
LED lamps are used to extend lamp life and save energy. \* Installed on the right or left side of the machine.



**Signal light (1, 2, or 3 lamps)**  
LED lamps are used. No maintenance required. Can be tilted to improve visibility.



**Automatic oil lubricator**  
Regularly applies oil to all lubricating points on the three axes.



**Automatic grease lubricator**  
Regularly applies grease to all lubricating points on the three axes. \* Manual greasing is required for the standard specification model.

- Coolant tank
  - 1) Coolant tank, 50L \*4
  - 2) Coolant tank, 100L \*4
  - 3) Coolant tank, 150L
  - 4) Coolant tank, 150L for 1.5 MPa CTS pump with cyclone filter
  - 5) Coolant tank, 200L for 1.5 MPa CTS pump with cyclone filter \*5
  - 6) Chip conveyor tank, 360L scraper type
  - 7) Chip conveyor tank, 360L scraper type for 1.5 MPa CTS pump with cyclone filter
  - 8) Chip conveyor tank, 415L hinge + scraper type
  - 9) Chip conveyor tank, 415L hinge + scraper type for 1.5 MPa CTS pump with cyclone filter
- Coolant through spindle (CTS) piping, Max. 3.0 MPa
- Coolant through spindle (CTS) piping, Max. 7.0 MPa
- Column coolant nozzle \*4
- Head coolant nozzle
- Chip shower
- Tool cleaning system
- Fixture shower valve unit \*4
- Cleaning gun
- Mesh basket for collecting chips (2 pcs.)
- Mist collector
- High column (150 mm, 250 mm)
- Top cover
- Side cover with transparent window, single side
- Folding door (two-door)
- Work light (1 lamp for right side, 1 lamp for left side)

- Signal light (1, 2, or 3 lamps)
- Automatic oil lubricator
- Automatic grease lubricator
- Automatic door with switch panel 10 holes
- Area sensor
- Side shutter \*5
- Switch panel (8 holes or 10 holes)
- Manual pulse generator with enable switch
- Connector and hook for manual pulse generator with enable switch
- Tool breakage detector, touch type
- Touch probe with basic measurement software
- Datum sphere for measurement
- Rotary table T-200Ad
- Additional axis cable (for 1 axis or 2 axes)
- RS232C 25-pin connector at control box
- Spindle override
- Master on circuit
- Data protection switch, key type
- Grip cover for 14/21/28-tool magazine
- Parts name sticker set
- Breaker handle cover
- Origin alignment mark
- 100V outlet in control box
- Power supply expansion 50A
- Transformer box
- Specified color

- Industrial network
  - 1) CC-Link, master station
  - 2) CC-Link, remote device station
  - 3) PROFIBUS DP, slave
  - 4) DeviceNet, slave
  - 5) PROFINET, slave
  - 6) EtherNet/IP, slave
- EXIO board assembly
  - 1) EXIO board, input 32/output 32, additional #1
  - 2) EXIO board, input 32/output 32, additional #2
- PLC programming software for D00
- Memory expansion 3 Gbytes \*1
- High accuracy mode BII (Look-ahead 1,000 blocks, smooth path offset)
- Submicron command \*1 \*2
- Interrupt type macro
- Rotary fixture offset
- Feature coordinates setting \*1 \*3
- Involute interpolation
- Vibration adjustment

\* For the 20,000min<sup>-1</sup> coolant through spindle specifications, dry machining may not possible depending on workpiece material. For further details, please contact your local distributor.

\* The type of coolant may have a significant influence on the machine's lifecycle. It is recommended to use high-lubricity (emulsion type) coolant. Do not use chemical solution type (synthetic type) coolant, as it may cause damage to the machine.

\* When using CTS (Coolant Through Spindle) function, do not use flammable coolant (ex. oil-based type).

\*1. Standard on the S300/S500/S700Xd2-5AX.  
\*2. When the submicron command is used, changing to the conversation language program is disabled.  
\*3. There are restrictions on the axis configuration.  
\*4. Cannot be selected for the S700Xd2-100T.  
\*5. Cannot be selected for the S300Xd2.

Machine specifications

Item	S300Xd2 S300Xd2 RD *9 S300Xd2-5AX S300Xd2-5AX RD *9		S500Xd2 S500Xd2 RD *9 S500Xd2-5AX S500Xd2-5AX RD *9		S700Xd2 S700Xd2 RD *9 S700Xd2-5AX S700Xd2-5AX RD *9		S700Xd2-100T S700Xd2-100T RD *9 S700Xd2-5AX/100T S700Xd2-5AX/100T RD *9		
	(S300/S500/S700Xd2) CNC-D00			(S300/S500/S700Xd2-5AX) CNC-D00v (DB)					
CNC unit									
X axis	mm(inch)	300 (11.8)	500 (19.7)		700 (27.6)		700 (27.6)		
Y axis	mm(inch)	450 (17.7)						450 (17.7)	
Z axis	mm(inch)	300 (11.8)	380 (15.0)	300 (11.8)	380 (15.0)	380 (15.0)			
Distance between table top and spindle nose end	mm(inch)	180-480 (7.1-18.9)	180-480 (7.1-18.9)	150-530 (5.9-20.9)	180-480 (7.1-18.9)	150-530 (5.9-20.9)	150-530 (5.9-20.9)		
Work area size	mm(inch)	600 x 450 (23.4 x 17.7)						800 x 450 (31.4 x 17.7)	
Max. loading capacity (uniform load)	kg(lbs)	250 [300 *6] [551 [661 *6]]		250 [400 *6] [551 [881 *6]]		250 [400 *6] [551 [881 *6]]			
Spindle speed *14	min <sup>-1</sup>	12,000min <sup>-1</sup> spec.: 1-12,000 10,000min <sup>-1</sup> high-torque spec. (optional): 1-10,000 27,000min <sup>-1</sup> spec. (optional): 1-27,000 (27,000min spec. cannot be selected for Z-axis 380 mm spec. models)						12,000min <sup>-1</sup> spec.: 1-12,000 10,000min <sup>-1</sup> high-torque spec. (optional): 1-10,000 20,000min <sup>-1</sup> spec. (optional): 1-20,000	
Speed during tapping	min <sup>-1</sup>	MAX 6,000 (27,000min <sup>-1</sup> spec.: MAX 8,000)						MAX 6,000	
Tapered hole		7/24 tapered NO.30						7/24 tapered NO.30	
BT dual contact spindle (BIG-PLUS)		Optional						Optional	
Coolant through spindle (CTS)		Optional (CTS cannot be selected for 27,000min <sup>-1</sup> spec. models)						Optional	
Rapid traverse rate (XYZ axes)	m/min(inch/min)	50 x 50 x 56 (1,969 x 1,969 x 2,205)						50 x 50 x 56 (1,969 x 1,969 x 2,205)	
Cutting feed rate	mm/min(inch/min)	X, Y, Z: 1-30,000 (0.04-1,181) *7						X, Y, Z: 1-30,000 (0.04-1,181) *7	
Tool shank type		MAS-BT30						MAS-BT30	
Pull stud type *4		MAS-P30T-2						MAS-P30T-2	
Tool storage capacity	pcs.	14 / 21		14 / 21 / 28		100 *12			
Max. tool length *1	mm(inch)	160 (6.3) [21 tool] 250 (9.8) [14 tool]		250 (9.8)		250 (9.8)			
Max. tool diameter *1	mm(inch)	110 (4.3)						Turret magazine: 110 (4.3), Tool stocker: 60 (2.3) / 110 (4.3) (No adjacent tool)	
Max. tool weight *1	kg(lbs)	3.0 (6.6) [4.0 (8.8)*10] / tool, <TOTAL TOOL WEIGHT: 25 (55.1) for 14 tools, 35 (77.2) for 21 or 28 tools>						Turret magazine: 3.0 (6.6) [4.0 (8.8)*10] / tool, <Total tool weight: 35 (77.2)> Tool stocker: 4.0 (8.8) / tool, <Total tool weight: 50 (110.2)>	
Tool selection method		Random shortcut method						Random shortcut method	
Tool To Tool	sec	0.6 / 0.7 (14 or 21 tools / 28 tools)						0.7 *13	
Chip To Chip	sec	Z-axis 300 mm spec.: 1.2 / 1.3 (14 or 21 tools / 28 tools) Z-axis 380 mm spec.: 1.3 / 1.4 (14 or 21 tools / 28 tools)						1.4 *13	
Main spindle motor (10min/continuous) *2	kW	12,000min <sup>-1</sup> spec.: 10.1/7.0 10,000min <sup>-1</sup> high-torque spec. (optional): 12.8/9.2 20,000min <sup>-1</sup> spec. (optional): 7.4/5.1 27,000min <sup>-1</sup> spec. (optional): 8.9/6.3						12,000min <sup>-1</sup> spec.: 10.1/7.0 10,000min <sup>-1</sup> high-torque spec. (optional): 12.8/9.2 20,000min <sup>-1</sup> spec. (optional): 7.4/5.1	
Axis feed motor	kW	X,Y axis: 1.0 Z axis: 2.0						X,Y axis: 1.0 Z axis: 2.0	
Power supply		200 to 230 VAC ±10%, 3phase, 50/60Hz±2%						200 to 230 VAC ±10%, 3phase, 50/60Hz±2%	
Power capacity (continuous)	kVA	12,000min <sup>-1</sup> spec.: 9.5 10,000min <sup>-1</sup> high-torque spec. (optional): 10.4 20,000min <sup>-1</sup> spec. (optional): 9.5 27,000min <sup>-1</sup> spec. (optional): 9.5						12,000min <sup>-1</sup> spec.: 9.5 10,000min <sup>-1</sup> high-torque spec. (optional): 10.4 20,000min <sup>-1</sup> spec. (optional): 9.5	
Air supply	Regular air pressure MPa Required flow L/min	0.4-0.6 (recommended value 0.5MPa *8) 40 (27,000min <sup>-1</sup> spec.: 115)						0.4-0.6 (recommended value 0.5MPa *8) 40	
Height	mm(inch)	Z-axis 300 mm spec.: 2,529 (99.6) Z-axis 380 mm spec.: 2,568 (101.1)						2,568 (101.1)	
Required floor space *11 (with control unit door open)	mm(inch)	1,080 x 2,161 [2,999] (42.5 x 85.1 [118.1])	1,560 x 2,081 [2,919] (61.4 x 81.9 [114.9])	2,050 x 2,081 [2,919] (80.7 x 81.9 [114.9])	2,050 x 2,081 [2,919] (80.7 x 81.9 [114.9])				
Weight [with BV7-870Ad]	kg(lbs)	2,350 (5,181) [2,650 (5,843)]	2,400 (5,292) [2,700 (5,953)]	2,550 (5,622)		2,700 (5,953)			
Accuracy *3	mm(inch) mm(inch)	0.006-0.020 (0.00024-0.00079)						0.006-0.020 (0.00024-0.00079)	
Repeatability of bidirectional axis positioning (ISO230-2:2014)	mm(inch)	Less than 0.004 (0.00016)						Less than 0.004 (0.00016)	
Front door		2doors							
Standard accessories		Instruction Manual (DVD 1 set), leveling bolts (4 pcs.), leveling plates (4 pcs.)							

\*1. The maximum tool length, maximum diameter, and maximum weight are limited depending on the spindle speed in use, configuration, center of gravity, etc. The figures shown here are for reference only. Please contact your local distributor for details. \*2. Spindle motor output differs depending on the spindle speed. \*3. Measured in compliance with ISO standards and Brother standards. Please contact your local distributor for details. \*4. Brother specifications apply to the pull studs for CTS. \*5. Measured in compliance with JIS B6336-9 and MAS011-1987. \*6. Parameter adjustment is required. (Acceleration adjustment and positioning speed are also changed according to the weight.) \*7. When using high accuracy mode B. \*8. Regular air pressure varies depending on the machine specifications, machining program details, or use of peripheral equipment. Set the pressure higher than the recommend value. \*9. The machine needs to be equipped with a relocation detection device depending on the destination. Machines equipped with a relocation detection device come with "RD" at the end of the model name. \*10. Parameter setting must be changed. (Tool indexing time will change.) Max. tool weight 4.0 kg cannot be available for the 27,000 min<sup>-1</sup> specifications. \*11. The value does not include the coolant tank. \*12. Value for turret magazine plus tool stocker \*13. Value for turret magazine \*14. The 16,000min<sup>-1</sup> specification is discontinued as of March 2026.

- Please read the instruction manuals and safety manuals before using Brother products for your own safety. When using oil-based coolant or when machining materials which can cause a fire (ex. magnesium, resin), customers are requested to take thorough safety measures against fire. The types of cutting material, cutting tools, coolant, or lubrication oil may have an influence on the machine's lifecycle. For further questions, please contact your local distributor.
- Leave 700 mm between machines as maintenance space.
- When exporting our machine together with additional 1-axis rotary table or compound rotary table (including cases where a rotary table is scheduled to be installed overseas), or exporting the S300/S500/S700Xd2-5AX, the machine is deemed to be included in the "applicable listed items" controlled by the Foreign Exchange and Foreign Trade Act of Japan. When exporting the machine, please obtain required permissions, including an export license, from the Ministry of Economy, Trade and Industry (METI) or Regional Bureaus of Economy, Trade and Industry before shipment. When re-selling or re-exporting the machine, you may need to obtain permissions from METI, and the government of the country where the machine is installed.
- When exporting our machine together with compound rotary table (including cases where a rotary table is scheduled to be installed overseas), as a machine conforming to Row 2 of Appended Table 1 of Export Trade Control Order, or exporting the S300/S500/S700Xd2-5AX, a relocation detection device is installed on the machine depending on the destination country. After relocating the machine with the detection device, the machine is locked and any operation is temporarily impossible. Please inform your local distributor of machine relocation in advance and apply to perform the release operation of relocated machine.
- In order to operate our machine with an additional axis rotary table installed separately overseas after exporting the machine, a procedure to activate the axis of the rotary table is needed. Please inform your local distributor of these processes in advance, because the predetermined procedure is required to perform the activation. In addition, for export to some countries and regions other than "Group A countries", it is not possible to install a compound rotary table separately overseas after exporting the machine. Please make sure you obtain an export license for the machine together with compound rotary table before shipment.

NC unit specifications

《S300Xd2/S500Xd2/S700Xd2》		《S300Xd2-5AX/S500Xd2-5AX/S700Xd2-5AX》	
CNC model	CNC-D00	CNC model	CNC-D00v (DB)
Control axes	5 axes (X, Y, Z, 2 additional axes)	Control axes	5 axes (X, Y, Z, 2 additional axes)
Simultaneously controlled axes (Positioning)	5 axes (X, Y, Z, 2 additional axes)	Simultaneously controlled axes (Positioning)	5 axes (X, Y, Z, 2 additional axes)
Simultaneously controlled axes (Interpolation)	Linear: 4 axes (X, Y, Z, 1 additional axis) Circular: 2 axes Helical/Conical: 3 axes (X, Y, Z)	Simultaneously controlled axes (Interpolation)	Linear: 5 axes (X, Y, Z, 2 additional axes) Circular: 2 axes Helical/Conical: 4 axes (3 linear axes + 1 additional axis, 2 linear axes + 2 additional axes)
Least input increment	0.001mm, 0.0001inch, 0.001 deg. 0.0001mm, 0.00001inch, 0.0001 deg. (optional)	Least input increment	0.0001 mm, 0.00001 inch, 0.0001 deg.
Max. programmable dimension	±999999.999mm, ±99999.9999inch ±999999.9999mm, ±99999.9999inch (optional)	Max. programmable dimension	±999999.9999 mm, ±99999.99999 inch
Display	15-inch color LCD touch display	Display	15-inch color LCD touch display (Total capacity of program and data bank)
Memory capacity	500 Mbytes, 3 Gbytes (optional) (Total capacity of program and data bank)	Memory capacity	3 Gbytes (Total capacity of program and data bank)
External communication	USB memory interface, Ethernet, RS232C (optional)	External communication	USB memory interface, Ethernet, RS232C (optional)
No. of registrable programs	4,000 (Total capacity of program and data bank)	No. of registrable programs	4,000 (Total capacity of program and data bank)
Program format	NC language, conversation language (changed by parameter) Conversion from conversation language program to NC language program available * Only NC language available on the S700Xd2-100T. Conversation language not available	Program format	NC language Conversation language not available

\* "Control axes" and "Simultaneously controlled axes" indicate the maximum number of axes, which will differ depending on the shipping destination or machine specifications.  
\* Ethernet is a registered trademark of Xerox Corporation in the United States.

NC functions

Operation	Dry run	Monitoring	Machining load monitoring	Standby mode	Mirror image
Machine lock	Machine lock	ATC tool monitoring	Automatic coolant off	Automatic work light off	External sub program call
Program restart	Program restart	Overload prediction	Chip shower off delay	Chip shower energy savings operation	Macro
Rapid traverse override	Rapid traverse override	Waveform display / Cutting feed override	Waveform output to memory card	Energy savings mode	Tape operation / FTP load operation
Background editing	Background editing	Automatic thermal distortion compensation (X, Y, and Z axes)	Production performance display	Adjust machine parameters	Multiple skip function
Screen shot	Screen shot	Operation level	Tool life / Spare tool	ATC tool	<Optional> Submicron command *2 *5
Operation level	Operation level	External input signal key	Stuck chips detection function	Tool life	Interrupt type macro
Shortcut key	Shortcut key	<Optional> Spindle override	Tap return function	Waveform display	Rotary fixture offset
Absolute / Incremental	Absolute / Incremental	Status log	Alarm log	Production performance	Feature coordinates setting *3 *5
Inch / Metric	Inch / Metric	Maintenance notice	Motor insulation resistance measurement	Energy saving/Power consumption	Involute interpolation
Coordinate system setting	Coordinate system setting	Corner C / Corner R	Tool cleaning filter with filter clogging detection	Recovery support	Vibration adjustment
Rotational transformation	Rotational transformation	Synchronized tap	Battery-free encoder	Inspection	Functions limited to conversation language *6
Subprogram	Subprogram	Graphic display	Brake load test	Machining support without warmup	Schedule program
Automatic workpiece measurement *1	Automatic workpiece measurement *1	Computer remote	Automatic power off	Software control panel	Automatic tool selection
Tool length measurement	Tool length measurement	OPC UA		File viewer	Automatic cutting condition setting
Machining parameter adjustment	Machining parameter adjustment	Auto notification		Notebook	Automatic tool length compensation setting
High accuracy mode All	High accuracy mode All	Built-in PLC (LD/ST/FBD)		Calculator	Automatic cutter compensation setting
High accuracy mode BI (look-ahead 160 blocks)	High accuracy mode BI (look-ahead 160 blocks)	<Optional> CC-Link, master station		Register shortcut	Automatic calculation of unknown number input
Backlash compensation	Backlash compensation	CC-Link, remote device station		Display off	Machining order control
Tool center point control *3 *4 (Look-ahead 1,000 blocks)	Tool center point control *3 *4 (Look-ahead 1,000 blocks)	PROFIBUS DP, slave		Menu programming	
<Optional> High accuracy mode BII (Look-ahead 1,000 blocks, smooth path offset)	<Optional> High accuracy mode BII (Look-ahead 1,000 blocks, smooth path offset)	DeviceNet, slave		Local coordinate system	
		PROFINET, slave		Expanded workpiece coordinate system	
		EtherNet/IP, slave		One-way positioning	
		Energy saving		Inverse time feed	
		Automatic power off		Programmable data input	
				Tool length compensation	
				Cutter compensation	
				Scaling	

\*1. For the measuring instrument, please select an optional touch probe or provide one yourself. \*2. When the submicron command is used, changing to the conversation language program is disabled. \*3. There are restrictions on the axis configuration. \*4. Available only on the S300/S500/S700Xd2-5AX. \*5. Standard on the S300/S500/S700Xd2-5AX. \*6. Conversation language not available on S300/S500/S700Xd2-5AX and S700Xd2-100T.



Machining capability

	ADC	Cast iron	Carbon steel
Drilling			
12,000min <sup>-1</sup>	D32 x 0.2 (1.26 x 0.008)	D28 x 0.15 (1.10 x 0.006)	D25 x 0.1 (0.98 x 0.004)
10,000min <sup>-1</sup> high-torque	D40 x 0.2 (1.57 x 0.008) D30 x 0.7 (1.18 x 0.028)	D34 x 0.15 (1.34 x 0.006) D26 x 0.4 (1.02 x 0.016)	D30 x 0.15 (1.18 x 0.006) D26 x 0.25 (1.02 x 0.010)
20,000min <sup>-1</sup>	D24 x 0.2 (0.94 x 0.008)	D23 x 0.15 (0.91 x 0.006)	D18 x 0.1 (0.71 x 0.004)
27,000min <sup>-1</sup>	D20 x 0.2 (0.79 x 0.008)	D19 x 0.15 (0.75 x 0.006)	D18 x 0.1 (0.71 x 0.004)
Tapping			
12,000min <sup>-1</sup>	M27 x 3.0 (1-8UNC)	M27 x 3.0 (1-8UNC)	M22 x 2.5 (7/8-9UNC)
10,000min <sup>-1</sup> high-torque	M39 x 4.0 (11/2-6UNC)	M33 x 3.5 (11/4-7UNC)	M27 x 3.0 (1-8UNC)
20,000min <sup>-1</sup>	M22 x 2.5 (7/8-9UNC)	M22 x 2.5 (7/8-9UNC)	M16 x 2.0 (5/8-11UNC)
27,000min <sup>-1</sup>	M22 x 2.5 (7/8-9UNC)	M20 x 2.5 (3/4-10UNC)	M12 x 1.75 (7/16-14UNC)
Facing			
12,000min <sup>-1</sup>	1,200: 100 x 4.0 x 3,000 (73.2: 3.94 x 0.16 x 118.1)	137: 40 x 6.0 x 573 (8.4: 1.57 x 0.24 x 22.6)	100: 40 x 5.2 x 484 (6.1: 1.57 x 0.20 x 19.1)
10,000min <sup>-1</sup> high-torque	1,920: 100 x 6.4 x 3,000 (117.2: 3.94 x 0.25 x 118.1)	303: 40 x 6.0 x 1,263 (18.5: 1.57 x 0.24 x 49.7)	256: 40 x 6.0 x 1,067 (15.6: 1.57 x 0.24 x 42.0)
20,000min <sup>-1</sup>	960: 100 x 3.2 x 3,000 (58.6: 3.94 x 0.13 x 118.1)	83: 40 x 3.6 x 573 (5.1: 1.57 x 0.14 x 22.6)	54: 40 x 2.8 x 484 (3.3: 1.57 x 0.11 x 19.1)
27,000min <sup>-1</sup>	600: 100 x 2.0 x 3,000 (36.6: 3.94 x 0.08 x 118.1)	45: 40 x 2.0 x 573 (2.7: 1.57 x 0.08 x 22.6)	30: 40 x 1.6 x 484 (1.8: 1.57 x 0.06 x 19.1)



\* Data obtained from tests conducted by Brother.

\* Please check the external views or interference diagrams provided by Brother when designing jigs or checking for interference.  
 \* Chip conveyors are available for all specifications.  
 \* 150L and 200L coolant tanks can be selected for the S700Xd2-100T, but 50L and 100L cannot be selected.


S300Xd2



S500Xd2






S700Xd2



S700Xd2-100T

\* Figure shows when chip conveyor is used.



**Brother Technology Center Chicago**

BROTHER INTERNATIONAL CORP.  
2200 North Stonington Avenue, Suite 270, Hoffman Estates, IL 60169, U.S.A.  
PHONE:(1)224-653-8415 FAX:(1)224-653-8821

**Brother Technology Center Frankfurt**

BROTHER INTERNATIONALE INDUSTRIEMASCHINEN GmbH  
Hoechst Str.94, 65835 Liederbach, Germany  
PHONE:(49)69-977-6708-0 FAX:(49)69-977-6708-80

**Brother Technology Center Bengaluru**

BROTHER MACHINERY INDIA PVT LTD.  
SB-111-112, 1st Stage, 2nd Cross, Peenya Indl Estate, Bengaluru - 560058 Karnataka, India  
PHONE:(91)80-4705-3355

**Brother Technology Center Pune**

BROTHER MACHINERY INDIA PVT LTD.  
Plot No. J20, M.I.D.C, Bhosari, Pimpri Chinchwad, Pune, Maharashtra, India  
PHONE:(91)020-69148000

**Brother Technology Center Dongguan**

BROTHER MACHINERY SHANGHAI LTD.  
Room 103, Building 1, No.2 Nanbo Road,  
Songshan Lake District, Dongguan City, Guangdong Province, China  
PHONE:(86)769-2238-1505 FAX:(86)769-2238-1506

**Brother Technology Center Ningbo**

BROTHER MACHINERY SHANGHAI LTD.  
1F, Building 1, No. 102, Hongtang South Road West Section, Jiangbei District, Ningbo City,  
Zhejiang Province, China  
PHONE:(86)574-87781232 FAX:(86)574-88139792

**Brother Technology Center Tianjing**

BROTHER MACHINERY SHANGHAI LTD.  
Room 102, Door 1, Building 2, (Xinhua International University Science and Technology Park)  
No.1 Huixue Road, Jingwu Town, Xiqing District, Tianjin, China  
PHONE:(86)22-5803-2395

**Brother Technology Center Queretaro**

BROTHER INTERNACIONAL DE MÉXICO, S.A. DE C.V.  
Calle 1 No.310 Int 15, Zona Industrial Jurica, Parque Industrial Jurica,  
Queretaro, QRO C.P. 76100 México  
PHONE:(52)55-8503-8760 FAX:(52)442-483-2667

**Brother Technology Center Bangkok**

BROTHER COMMERCIAL (THAILAND) LTD.  
317 Pattanakarn Road, Pravet Sub-District, Pravet District, Bangkok 10250, Thailand  
PHONE:(66)2321-5910 FAX:(66)2321-5913

**Brother Technology Center Gurugram**

BROTHER MACHINERY INDIA PVT LTD.  
Plot No. 60, Sector 34, HSIIDC, Gurugram, Haryana 122001, India  
PHONE:(91)0124-4449900

**Brother Technology Center Shanghai**

BROTHER MACHINERY SHANGHAI LTD.  
Unit 01, 5/F., No.799, West Tianshan Rd., ChangNing District Shanghai 200335, China  
PHONE:(86)21-2225-6666 FAX:(86)21-2225-6688

**Brother Technology Center Chongqing**

BROTHER MACHINERY SHANGHAI LTD.  
Room 30, 31, NO.104 Cui bai Road, Dadukou District, Chongqing Province, 400084, China  
PHONE:(86)23-6865-5600 FAX:(86)23-6865-5560

**Brother Technology Center Nanjing**

BROTHER MACHINERY SHANGHAI LTD.  
Room 106, Building 02, Tian An Cyber Park, No.36, Yongfeng Avenue, Qinhuai District,  
Nanjing City, Jiangsu Province, China  
PHONE:(86)25-87185503 FAX:(86)25-8718-5503

Figures in brackets ( ) are the country codes.

Specifications may be subject to change without any notice.

**BROTHER INDUSTRIES, LTD.**

**Machinery Business Division**

1-5, Kitajizoyama, Noda-cho, Kariya-shi, Aichi-ken 448-0803, Japan  
<https://www.brother.co.jp>



Please check here for detailed information  
and the latest information of the base.

<https://machinetool.global.brother/>

